

Pelican Classic Rack Cases Catalog

Classic Rack™	Rack Height U Size			Rack Length		Rack Width		Lid i.d. Front / Back 1	Length o.d. 2		Width o.d.		Height o.d. 3		Weight		Shipping Cube	
	Part Number	u	in	mm	in	mm	in	mm	in	in	mm	in	mm	in	mm	lbs	kg	ft3
de2410-02/24/02	3u	5.25	133	20	508	19	483	2.5 / 2.5	32.0	813	27.0	686	12.3	311	43	19.5	6.1	0.17
de2410-02/24/05								2.5 / 5.25	34.8	883					44	20.0	6.7	0.19
de2410-05/24/05								5.25 / 5.25	37.5	953					45	20.4	7.2	0.20
de2412-02/24/02	4u	7.00	178	20	508	19	483	2.5 / 2.5	32.0	813	27.0	686	14.6	371	50	22.7	7.3	0.21
de2412-02/24/05								2.5 / 5.25	34.8	883					51	23.1	7.9	0.22
de2412-05/24/05								5.25 / 5.25	37.5	953					52	23.6	8.6	0.24
de2414-02/24/02	5u	8.75	222	20	508	19	483	2.5 / 2.5	32.0	813	27.0	686	16.6	422	52	23.6	8.3	0.24
de2414-02/24/05								2.5 / 5.25	34.8	883					54	24.5	9.0	0.26
de2414-05/24/05								5.25 / 5.25	37.5	953					56	25.4	9.7	0.28
de2414-02/27/02	5u	8.75	222	25	635	19	483	2.5 / 2.5	34.9	886	27.0	686	16.6	422	53	24.0	9.1	0.26
de2414-02/27/05								2.5 / 5.25	37.6	956					55	24.9	9.8	0.28
de2414-05/27/05								5.25 / 5.25	40.4	1026					57	25.9	10.5	0.30
de2416-02/24/02	6u	10.50	267	20	508	19	483	2.5 / 2.5	32.0	813	27.0	686	18.6	473	56	25.4	9.3	0.26
de2416-02/24/05								2.5 / 5.25	34.8	883					57	25.9	10.1	0.29
de2416-05/24/05								5.25 / 5.25	37.5	953					59	26.8	10.9	0.31
de2416-02/27/02	6u	10.50	267	25	635	19	483	2.5 / 2.5	34.9	886	27.0	686	18.6	473	57	25.9	10.1	0.29
de2416-02/27/05								2.5 / 5.25	37.6	956					59	26.8	10.9	0.31
de2416-05/27/05								5.25 / 5.25	40.4	1026					60	27.2	11.7	0.33
de2418-02/20/02	7u	12.25	311	18	457	19	483	2.5 / 2.5	27.5	699	27.0	686	20.6	524	59	26.8	8.9	0.25
de2418-02/20/05								2.5 / 5.25	30.3	768					61	27.7	9.7	0.28
de2418-05/20/05								5.25 / 5.25	33.0	838					63	28.6	10.6	0.30
de2418-02/27/02	7u	12.25	311	25	635	19	483	2.5 / 2.5	34.9	886	27.0	686	20.6	524	60	27.2	11.2	0.32
de2418-02/27/05								2.5 / 5.25	37.6	956					62	28.1	12.1	0.34
de2418-05/27/05								5.25 / 5.25	40.4	1026					64	29.0	13.0	0.37
de2421-02/27/02	9u	15.75	400	25	635	19	483	2.5 / 2.5	34.9	886	27.0	686	24.3	616	70	31.8	13.2	0.37
de2421-02/27/05								2.5 / 5.25	37.6	956					71	32.2	14.3	0.40
de2421-05/27/05								5.25 / 5.25	40.4	1026					73	33.1	15.3	0.43

Classic Rack™	Rack Height U Size			Rack Length		Rack Width		Lid i.d. Front / Back 1	Length o.d. 2		Width o.d.		Height o.d. 3		Weight		Shipping Cube	
Part Number	u	in	mm	in	mm	in	mm	in	in	mm	in	mm	in	mm	lbs	kg	ft3	m3
* de2121-02/18/02	10u	17.50	445	17	432	19	483	2.5 / 2.5	25.5	648	24.0	610	24.3	616	47	21.3	8.6	0.24
* de2121-02/18/05								2.5 / 5.25	28.3	718					49	22.2	9.5	0.27
* de2121-05/18/05								5.25 / 5.25	31.0	787					51	23.1	10.4	0.30
* de2121-02/30/02	10u	17.50	445	28	711	19	483	2.5 / 2.5	37.5	953	24.0	610	24.3	616	76	34.5	12.6	0.36
* de2121-02/30/05								2.5 / 5.25	40.3	1022					78	35.4	13.6	0.38
* de2121-05/30/05								5.25 / 5.25	43.0	1092					80	36.3	14.5	0.41
de2425-02/27/02	11u	19.25	489	25	635	19	483	2.5 / 2.5	34.9	886	27.0	686	27.9	709	75	34.0	15.2	0.43
de2425-02/27/05								2.5 / 5.25	37.6	956					78	35.4	16.4	0.46
de2425-05/27/05								5.25 / 5.25	40.4	1026					81	36.7	17.6	0.50
de2430-02/27/02	14u	24.50	622	25	635	19	483	2.5 / 2.5	34.9	886	27.0	686	33.0	838	79	35.8	18.0	0.51
de2430-02/27/05								2.5 / 5.25	37.6	956					81	36.7	19.4	0.55
de2430-05/27/05								5.25 / 5.25	40.4	1026					83	37.6	20.8	0.59
de2442-02/27/02	21u	36.75	933	25	635	19	483	2.5 / 2.5	34.9	886	27.0	686	44.6	1133	103	46.7	24.3	0.69
de2442-02/27/05								2.5 / 5.25	37.6	956					105	47.6	26.2	0.74
de2442-05/27/05								5.25 / 5.25	40.4	1026					107	48.5	28.2	0.80
de2652-02/25/02	26u	45.50	1156	23	584	19	483	2.5 / 2.5	32.5	826	29.0	737	54.6	1387	119	54.0	29.8	0.84
de2652-02/25/05								2.5 / 5.25	35.3	895					121	54.9	32.3	0.91
de2652-05/25/05								5.25 / 5.25	38.0	965					123	55.8	34.8	0.99
de2410-02/35/02 neW	3u	5.25	133	33	838	19	483	2.5 / 2.5	43.0	1092	27.0	686	12.3	311	50.0	22.7	8.3	0.24
de2410-02/35/05 neW								2.5 / 5.25	45.8	1163					51.0	23.1	8.8	0.25
de2410-05/35/05 neW								5.25 / 5.25	48.5	1232					52.0	23.6	9.3	0.26
de2412-02/35/02 neW	4u	7.00	178	33	838	19	483	2.5 / 2.5	43.0	1092	27.0	686	14.6	371	53.0	24.0	9.8	0.28
de2412-02/35/05 neW								2.5 / 5.25	45.8	1163					54.0	24.5	10.5	0.30
de2412-05/35/05 neW								5.25 / 5.25	48.5	1232					55.0	25.0	11.1	0.31
de2414-02/35/02 neW	5u	8.75	222	33	838	19	483	2.5 / 2.5	43.0	1092	27.0	686	16.6	422	54.0	24.5	11.2	0.32
de2414-02/35/05 neW								2.5 / 5.25	45.8	1163					56.0	25.4	11.9	0.37
de2414-05/35/05 neW								5.25 / 5.25	48.5	1232					58.0	26.3	12.6	0.36
de2418-02/35/02 neW	7u	12.25	311	33	838	19	483	2.5 / 2.5	43.0	1092	27.0	686	20.6	524	63.0	28.6	13.8	0.39
de2418-02/35/05 neW								2.5 / 5.25	45.8	1163					65.0	29.5	14.7	0.42
de2418-05/35/05 neW								5.25 / 5.25	48.5	1232					67.0	30.4	15.6	0.44
de2421-02/35/02 neW	9u	15.75	400	33	838	19	483	2.5 / 2.5	43.0	1092	27.0	686	24.3	616	71.0	32.2	16.3	0.46
de2421-02/35/05 neW								2.5 / 5.25	45.8	1163					72.0	32.7	17.4	0.49
de2421-05/35/05 neW								5.25 / 5.25	48.5	1232					74.0	33.6	18.4	0.52

* Reduced sway space – special shock mounts required 1 – lid outside dimension (o.d.) = lid i.d. plus 1.25" per lid
 2 – length includes stacking ribs 3 – height excludes 1.0" stacking ribs